

Material Safety Data Sheet



1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product Name : Capcem PLG
Application : Pumpable cement grout for full column grouting of mechanical long anchors.
Company : Minova RSA
Address : P.O. Box 52, Isando, 1600.
Telephone : (011) 908-1980 **Telefax** : (011) 864-4311

2. COMPOSITION / INFORMATION ON INGREDIENTS

Composition : Cements, PFA, Hydrated Lime, Additives.

Hazardous Ingredient(s)	Symbol	Risk Phrases	Other Information	%
Cements (OPC)	Xi	R36/37/38	Cas No: 65997-15-1	<35%
Pulverised Fuel Ash		See Section 8	Cas No: -----	>25<50%
Calcium hydroxide	Xi	R38, 41	Cas No: 1305-62-0	<3%

All constituents of this product are listed in EINECS (European Inventory of Existing Commercial Chemical Substances) or ELINCS (European List of New Chemical Substances) or are exempt. Refer to Section 8 for Occupational Exposure Limits.

3. HAZARDS IDENTIFICATION

Irritating to eyes, respiratory system and skin.

IRRITANT

4. FIRST AID MEASURES

Eyes : Irrigate immediately with copious quantities of water for several minutes. Obtain medical attention urgently.
Skin : Wash immediately with copious quantities of water. Remove contaminated clothing immediately. Obtain medical advice if skin disorders develop.
Inhalation : Remove from exposure, if feeling unwell obtain medical attention.
Ingestion : Wash out mouth with water. **DO NOT** induce vomiting. Obtain medical attention.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media : None, not flammable.
Special Exposure Hazards : None.
Special Protective Equipment : None.

=====

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions** : Wear rubber boots in addition to the recommended protective clothing.
- Environmental Precautions** : Prevent entry into drains, sewers and water courses.
- Decontamination Procedures** : Avoid the creation of dust in atmosphere. Gather into containers. Residues may be flushed to drain with large volumes of water.

=====

7. HANDLING AND STORAGE

- Handling** : Avoid creating dust. Avoid breathing dust, in case of insufficient ventilation, wear suitable respiratory equipment. Avoid skin and eye contact.
- Storage** : Store in a cool, dry area.

=====

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Occupational Exposure Limits :-			
Substance	8 Hour TWA	STEL	Source/Other Information
Portland Cement			EH 40
Total inhalable dust	10mgm ⁻³	---	
Respirable dust	5mgm ⁻³	---	
Calcium hydroxide			EH 40
Total inhalable dust	10mgm ⁻³	---	
Respirable dust	4mgm ⁻³	---	

- Engineering Control Measures** : Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.
- Personal Protective Equipment** : Impervious gloves (eg PVC). Goggles / Safety Glasses. Approved dust mask. Change contaminated clothing immediately and clean before re-use.

=====

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	:	Powder.
Colour	:	Grey.
Odour	:	Odourless.
pH (concentrate)	:	>12.
pH (working dilution)	:	Not applicable.
Boiling Point / Range (°C)	:	Not applicable.
Melting Point / Range (°C)	:	Not applicable.
Flash Point (closed, °C)	:	None.
Autoflammability (°C)	:	Not applicable.
Viscosity (at 20°C)	:	Not applicable.
Explosive Properties (%)	:	Not applicable.
Oxidising Properties	:	Not determined.
Vapour Pressure (kPa at 20°C)	:	Not applicable.
Relative Density (at 20°C)	:	1.3 (loose bulk)
Water Solubility	:	Insoluble.
Fat Solubility	:	Not applicable.
Partition Coefficient (noctanol / water)	:	Not applicable.
Other data	:	None.

=====

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Conditions to avoid	:	Exposure to air, contamination with water.
Materials to avoid	:	Strong acids.
Hazardous Decomposition Products	:	None.

=====

11. TOXICOLOGICAL INFORMATION

Health Effects

On Eyes	:	Irritating and may injure eye tissue if not removed promptly.
On Skin	:	Irritation. See "Chronic" effects.
By Inhalation	:	Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.
By Ingestion	:	May cause irritation of mouth, throat and digestive tract.
Chronic	:	Cement, cementitious grouts and mortars are known to cause both irritant and allergic contact dermatitis.

=====

12. ECOLOGICAL INFORMATION

Environmental Assessment	:	Little detailed information is available on the ecological effects of this product, but its overall environmental impact is not regarded as significant.
Mobility	:	Insoluble in water.
Persistence and Degradability	:	Not readily biodegradable.
Bioaccumulative Potential	:	Not expected to be bioaccumulative.
Ecotoxicity	:	Not expected to be ecotoxic to fish/daphnia/algae.

=====

13. DISPOSAL CONSIDERATIONS

Disposal must be in accordance with local and national legislation.

- Unused Product** : Disposed of in an approved manner.
- Used/Contaminated Product** : As for Unused product.
- Packaging** : The method of disposal must be acceptable to the local authority.

=====

14. TRANSPORT INFORMATION

This product is NOT classified as dangerous for transport.

=====

15. REGULATORY INFORMATION

- Hazard Label Data** :-
- Named Ingredients** : Cement Powders
- Symbol(s)** : Xi
- Risk Phrases** : Irritating to eyes, respiratory system and skin..
- Safety Phrases** : Do not breathe dust.
Avoid contact with skin and eyes.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Wear suitable gloves and eye / face protection.
- EC Directives** : Dangerous Substances Directive, 67/548/EEC and adaptations.
Dangerous Preparations Directive, 88/379/EEC.
Safety Data Sheets Directive, 91/155/EEC.
- Statutory Instruments** : Chemicals (Hazard Information and Packaging for Supply) (Amendment) Regs. 1999 (SI 1092).
Health & Safety at Work etc. Act 1974.
Control of Substances Hazardous to Health Regs. 1999 (SI 3246).
- Codes of Practice** : Waste Management. The Duty of Care.
- Guidance Notes** : Occupational skin diseases : Health and Safety Precautions (EH 26).
Dust in the workplace : general principles of protection (EH 44).
Occupational exposure limits (EH 40).

=====

16. OTHER INFORMATION

Minova RSA is an ISO 9002 accredited company.

The data advice given apply when the product is used for the stated application or applications. The product is not sold as suitable for any other application. Use of the product for applications other than as stated in this sheet may give rise to risks not mentioned in this sheet. The product should not be used other than for the stated application or applications without seeking advice from Minova RSA.

If this product has been purchased for supply to a third party for use at work, it is the purchaser's duty to take all necessary steps to secure that any person handling or using the product is provided with the information in this sheet.

It is the responsibility and duty of the employer to inform employees and others who may be affected of any hazards described in this sheet and of any precautions which should be taken.

This sheet does not constitute or substitute for the users own assessment of workplace risk, as required by other health and safety legislation.