

## Low density cement foam

### Uses

Tekseal S is used for void filling where longer flow distances and good penetration of loose fallen rock are required.

Typical applications of Tekseal S are the following:-

- Cavity filling after falls of ground.
- Construction of ventilation walls.

### Advantages

- High yield improves material handling logistics and cost.
- Rapid placement reduces man shifts - typically 50m<sup>3</sup> void filled per shift.
- Remote placement can take place up to 100m from machine.
- Maximum of 5 people per crew.
- Non-flammable, non-toxic, cement based.

### Description

Tekseal S is a single component cement foam. It is supplied as a powder which forms a cement foam on mixing with water in a purpose designed placer.

### Properties

**Water/solids ratio, w/s:** 0.8:1 - 1:1

**Pump life/set time:** Maximum pump life is ± 15 minutes, rate of set and strength development will depend on temperature and w/s used.

**Relative density (wet):** 0.35 - 0.45 depending on foam machine settings.

**Compressive strength:** 0.35 MPa  
(28 days, density = 0.35)

### Application Instructions

Tekseal must only be placed using a purpose designed placer at the stipulated water: solids ratio. TEKSEAL can be placed in remote areas via a 100m plastic or rubber pipe.

Large cavities can be filled using standpipes.

### Cleaning

All tools and equipment must be washed with water immediately after use.

## Estimating

Pack Size (kg)	Mix Water (litres)	Volume Yield (litres)
25	20	128

## Storage/Shelf Life

Tekseal S has a shelf life of 12 months when stored in cool, dry conditions, avoid storage in direct sunlight to prevent degradation of packaging.

## Precautions

### Health and Safety

Tekseal S is alkaline. The use of gloves and goggles is recommended. Splashes must be removed from the skin and eyes by washing with clean water. In case of splashes in the eyes, medical attention should be sought immediately. Refer to Material Safety Data Sheet.

## Technical Support

Minova RSA provides a technical advisory service by a team of specialists in the field. The service includes on site assistance and advice on evaluation trials and laboratory work.

## Additional information

Minova RSA is a market leader specialising in the supply of high performance chemical products for the mining and tunnelling industries.

Minova RSA range of mining products includes anchoring and backfill systems, bagged cement products, high yield grouts, mine sealants, equipment and accessories.

## Important note

Minova RSA products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Minova RSA endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

Minova RSA  
Reg. No. 2001/027226/07, ISO 9001:2000 Company

**Minova RSA**

trading name of Stratabolt (Pty) Ltd

Reg No. 2001/027226/07

Cnr Anvil & Brewery Roads

Isando

P.O. Box 52

Isando, 1600. South Africa

Tel: +27 (11) 923-1900

Fax: +27 (11) 923-1935

Email: [info@minovarsa.co.za](mailto:info@minovarsa.co.za)

Web: [www.minovainternational.com](http://www.minovainternational.com)



A member of the Orica Group

® trade mark of MINOVA RSA